

## GENERAL INFORMATION

### HEX NUT™

Internally Threaded Expansion Anchor

#### MATERIALS

Steel or stainless steel (A 2).

#### VERSION


- Steel with resistance class 8, natural finish or galvanized.
- Steel with resistance class 10, natural finish or galvanized.
- Steel with resistance class 12, natural finish.
- Stainless steel A 2-70, natural finish.

#### INDICATION

The strength class of the nut must always be equal to or greater than the class of resistance of the screw. That is, to a screw with resistance class 8.8 corresponds a nut with resistance class 8 (or higher, but never lower).



#### TECHNICAL SPECIFICATIONS




ø D	1.1/8	1.1/4	1.1/2	1.3/4	2
P	8	8	8	8	8
H	28,93	31,78	38,23	44,67	51,13
F	1.13/16 (46,02)	2 (50,80)	2.3/8 (60,33)	2.3/4 (69,85)	3.1/8 (79,38)

#### MEASUREMENTS

ø D	072	080	096	112	128
	1.1/8-8	1.1/4-8	1.1/2-8	1.3/4-8	2-8
	UNC TN 2H				
0000					

#### TECHNICAL SPECIFICATIONS



ø D	1/2	5/8	3/4	7/8	1	1.1/8	1.1/4	1.1/2	1.3/4	2
P	13	11	10	9	8	7	7	6	5	4,5
H	12,80	16,03	19,25	22,48	25,70	28,93	31,78	38,23	44,67	51,13
F	7/8 (22,23)	1.1/16 (26,97)	1.1/4 (31,75)	1.7/16 (36,53)	1.5/8 (41,28)	1.13/16 (46,02)	2 (50,80)	2.3/8 (60,33)	2.3/4 (69,85)	3.1/8 (79,38)

#### MEASUREMENTS

ø D	032	040	048	056	064	072	080	096
	1/2-13	5/8-11	3/4-10	7/8-9	1-8	1.1/8-7	1.1/4-7	1.1/2-6
	UNC TN 2H							
0000								

ø D	032	040	048	056	064
	1/2-13	5/8-11	3/4-10	7/8-9	1-8
	UNC GA 2H				
0000					